

# Micro-fit® Manifold

Micro-fit manifold works with optimal hardware and consumables especially suitable for Ascle U filtration funnel and Ascle V filtration unit. It has the same features with traditional manifold besides it is more flexible and has light structure.

## Features

- ◆ Whole equipment body is designed with stainless steel, surface is minor finished and is easy to clean and sterilize.
- ◆ Triplet filtering head design can be simultaneously suction filtration to improve work efficiency.
- ◆ Filtering head can quickly sterilize via flame for continuous lab operation.
- ◆ Filtering head can be easily dismounting and mounting and individual do moist heat sterilization
- ◆ Multiple filtering heads are available for two kinds of two kinds of membrane specification at 47mm



## Sterilization

- ◆ By autoclaving(max, 134°C)
- ◆ By dry heat sterilization(max, 180°C)
- ◆ By flaming

## Ordering Information

|                                | Cat. No. | Applicable membrane diameter | Dimension        | Weight  |
|--------------------------------|----------|------------------------------|------------------|---------|
| Micro-fit SS Manifold, 1-place | M101SS   | 47mm                         | 21.75x10.3x12 cm | 0.75 kg |
| Micro-fit SS Manifold, 3-place | M301SS   | 47mm                         | 43.5x10.3x12 cm  | 1.5 kg  |